

 **TRIANGLE TIRE**

Make your Move



2018 Ultra High Performance Tires Product Guide

Triangle Tire USA

Triangle Tire USA was established in January 2016 to provide high quality, innovative tire products at competitive prices to the American market. We offer a comprehensive product portfolio and a growing distribution network to service the needs of the market.

We service the commercial industry with an extensive line of dependable and fuel efficient medium radial tire products for the trucking industry, as well as a full range of premium quality radial and bias Off the Road (OTR) products for construction, mining and aggregate operations.

And for the consumer, we have a wide-ranging line up of passenger and light truck tires including ultra-high performance, winter tires and specialty trailer tires.

At Triangle, our goal is to be the Premier Value Provider to the tire industry. We are currently partnering with exceptional distribution partners to help us build an extensive network that will make the Triangle brand easily accessible and widely available anytime and anywhere there is a need.

Part of an Innovative and Growing Global Company

Triangle Tire USA is part of Triangle Tyre Co. Ltd., a global company that manufactures more than 25 million tires annually in 5,200 different SKUs (tread patterns and sizes). Triangle tire products are now sold in more than 180 countries around the world.

All Triangle tires are innovative, high-quality products due to the company's unrelenting commitment to research and development, as well as utilization of highly advanced, cutting edge, manufacturing technologies. The Triangle Tyre company boasts more than 360 patents, with research centers in Weihai (China), Akron, OH, and Germany. The Triangle Tire Technical Center in Akron was established in 2011 and works closely with Triangle Tire USA to develop relevant tread patterns, tire construction and custom polymer compounds designed specifically for American applications.

Triangle's "smart" plants are efficiently controlled by computer-integrated manufacturing systems for optimum quality control. We are currently working on exciting modern technologies such as the "smart tire" which will have a built-in chip that monitors and collects information such as road condition, temperature and tire damages for not only superior performance but for our customers' overall safety as well.

When you invest in a Triangle Tire product, you can do so with confidence that it is the result of a fully committed R&D philosophy and that it was manufactured with the highest standards and quality controls in the industry.

So, whether you need tires for your personal or business use, or if you are interested in joining the fastest growing distribution network in the industry . . . we would love to help you "*Make Your Move*" and come over to Triangle Tire.



TH201

SPORTEX

PAGES 4-5



TR968

PAGE 6-8



TR967

PAGES 9-10



TH201

SPORTEX




Outstanding Performance with Great Comfort

- Advanced large-block design with premium tread compound provides superior dry handling
- Optimized grooves design offers enhanced stopping on wet and dry conditions
- Asymmetric tread pattern with optimized pitch sequence help reduces excessive road noise

PRODUCT CODE	SIZE	LOAD RANGE	SPEED RATING	TREAD DEPTH [32NDS]	SECTION WIDTH [IN]	OVERALL DIAMETER [IN]	MAX LOAD [IN]	MAX PRESSURE [PSI]	UTQG
10122010371	195 / 45R16	84	W	8.0	7.68	22.91	1102	49	
10122010821	205 / 40R16	83	W	8.0	8.35	22.44	1074	49	
10122010380	205 / 50R16	91	W	8.0	8.43	24.09	1356	49	
10122010290	205 / 55R16	94	V	8.0	8.43	24.88	1477	49	
10122010631	225 / 50R16	96	W	8.0	9.17	24.88	1565	49	
10122010550	205 / 40R17	84	W	8.0	8.35	23.46	1102	49	
10122010491	205 / 50R17	93	W	8.0	8.43	25.12	1433	49	
10122010421	215 / 40R17	87	W	8.0	8.58	23.78	1202	49	
10122010570	215 / 45R17	91	W	8.0	8.39	24.65	1356	49	
10122010310	215 / 50R17	95	W	8.0	8.90	25.51	1521	49	
10122010080	215 / 55R17	94	W	8.0	8.90	26.30	1477	51	
10122010580	225 / 45R17	94	W	8.0	8.86	24.96	1477	49	
10122010250	225 / 50R17	98	W	8.0	9.17	25.91	1653	49	
10122010450	225 / 55R17	101	W	8.0	9.17	26.77	1819	49	
10122010390	235 / 45R17	97	Y	8.0	9.29	25.35	1609	49	

TH201 SPORTEX | CONTINUED

PRODUCT CODE	SIZE	LOAD RANGE	SPEED RATING	TREAD DEPTH [32NDS]	SECTION WIDTH [IN]	OVERALL DIAMETER [IN]	MAX LOAD [IN]	MAX PRESSURE [PSI]	UTQC
10122010160	245 / 45R17	99	Y	8.0	9.57	25.67	1709	49	
10122010001	215 / 35R18	84	Y	8.0	8.58	23.90	1102	49	
10122010751	225 / 40R18	92	Y	8.0	9.06	25.08	1389	49	
10122010780	235 / 40R18	95	Y	8.0	9.49	25.39	1521	49	
10122010530	235 / 45R18	98	Y	8.0	9.29	26.34	1653	49	
10122010851	245/40R18	97	Y	8.0	9.76	25.71	1609	49	
10122010900	245 / 40R18	97	W	8.0	9.76	25.71	1609	49	
10122010511	245 / 45R18	100	W	8.0	9.57	26.65	1764	49	
10122010640	265 / 35R18	97	Y	8.0	10.67	25.31	1609	49	
10122010150	215 / 35R19	85	W	10.0	8.58	24.92	1135	49	
10122010121	215 / 35R19	85	Y	10.0	8.58	24.92	1135	49	
10122010220	235 / 35R19	91	W	8.0	9.49	25.47	1356	49	
10122010480	235 / 35R19	91	Y	8.0	9.49	25.47	1356	49	
10122010350	245 / 35R19	93	Y	8.0	9.76	25.79	1433	49	
10122010141	265 / 30R19	93	Y	8.0	10.67	25.31	1433	49	
10122010131	275 / 30R19	96	Y	8.0	10.94	25.55	1565	49	
10122010771	245 / 35R20	95	Y	8.0	9.76	26.77	1521	49	
10122010941	255 / 35R20	97	Y	8.0	10.24	27.01	1609	49	
10122010671	265 / 40R20	104	W	8.0	10.67	28.35	1984	49	
10122010111	255 / 30R22	95	Y	8.0	10.24	28.07	1521	49	
10122010931	265 / 35R22	102	Y	8.0	10.67	29.33	1874	49	
10122010670	295 / 35R24	110	W	8.0	11.85	32.13	2337	49	
10122010681	305 / 35R24	112	W	8.0	12.32	32.44	2469	49	



TR968



Premium Ultra High Performance Tire

- Optimized tread design offers excellent high speed stability and great handling
- Enhanced sidewall rim protection provides longer tread life
- Premium compound help reduce excessive road noise

PRODUCT CODE	SIZE	LOAD RANGE	SPEED RATING	TREAD DEPTH [32NDS]	SECTION WIDTH [IN]	OVERALL DIAMETER [IN]	MAX LOAD [IN]	MAX PRESSURE [PSI]	UTQG
10129680560	205 / 40R16	83	V	10	8.35	22.44	1074	51	360 AA
10129680020	205 / 50R16	91	V	10	8.43	24.09	1356	51	360 AA
10129680750	205 / 55R16	91	H	10	8.43	24.88	1356	51	360 AA
10129680470	205 / 55R16	91	V	10	8.43	24.88	1356	51	360 AA
10129680120	225 / 50R16	96	V	10	9.17	24.88	1565	51	360 AA
10129680330	205 / 40R17	84	V	10	8.35	23.46	1102	51	360 AA
10129680430	205 / 50R17	89	V	10	8.43	25.12	1279	51	360 AA
10129680700	205 / 50R17	93	W	10	8.43	25.12	1433	51	360 AA
10129680070	215 / 40R17	83	V	10	8.58	23.78	1074	51	360 AA
10129680260	215 / 45R17	91	V	10	8.39	24.65	1356	51	360 AA
10129680520	215 / 45R17	91	W	10	8.39	24.65	1356	51	360 AA
10129680930	215 / 50R17	95	V	10	8.9	25.51	1521	51	360 AA
10129680680	215 / 50R17	95	W	10	8.9	25.51	1521	51	360 AA
10129680300	215 / 55R17	98	V	10	8.9	26.3	1653	51	360 AA
10129680270	225 / 45R17	94	V	10	8.86	24.96	1477	51	360 AA

TR968 | CONTINUED

PRODUCT CODE	SIZE	LOAD RANGE	SPEED RATING	TREAD DEPTH [32NDS]	SECTION WIDTH [IN]	OVERALL DIAMETER [IN]	MAX LOAD [IN]	MAX PRESSURE [PSI]	UTQG
10129680450	225 / 45R17	94	W	10	8.86	24.96	1477	51	360 AA
10129680780	225 / 50R17	98	V	10	9.17	25.91	1653	51	360 AA
10129680060	225 / 55R17	101	V	10	9.17	26.77	1819	51	360 AA
10129680660	235 / 45R17	97	V	10	9.29	25.35	1609	51	360 AA
10129680730	235 / 45R17	97	W	10	9.29	25.35	1609	51	360 AA
10129680250	245 / 45R17	99	V	10	9.57	25.67	1709	51	360 AA
10129680000	245 / 45R17	99	V	10	9.57	25.67	1709	51	360 AA
10129680980	215 / 35R18	84	V	10	8.58	23.9	1102	51	360 AA
10129680940	225 / 40R18	88	V	10	9.06	25.08	1235	51	360 AA
10129680090	225 / 40R18	92	V	10	9.06	25.08	1389	51	360 AA
10129680670	235 / 40R18	95	V	10	9.49	25.39	1521	51	360 AA
10129680740	235 / 40R18	95	W	10	9.49	25.39	1521	51	360 AA
10129680720	235 / 45R18	98	V	10	9.29	26.34	1653	51	360 AA
10129680380	245 / 40R18	97	V	10	9.76	25.71	1609	51	360 AA
10129680760	245 / 45R18	96	V	10	9.57	26.65	1565	51	360 AA
10129680480	265 / 35R18	93	V	10	10.67	25.31	1433	51	360 AA
10129680570	215 / 35R19	85	V	10	8.58	24.92	1135	51	360 AA
10129680100	235 / 35R19	91	V	10	9.49	25.47	1356	51	360 AA
10129680340	235 / 35R19	91	W	10	9.49	25.47	1356	51	360 AA
10129680990	245 / 35R19	93	V	10	9.76	25.79	1433	51	360 AA
10129680920	245 / 35R19	93	W	10	9.76	25.79	1433	51	360 AA
10129680650	265 / 30R19	93	V	10	10.67	25.31	1433	51	360 AA

TR968 | CONTINUED

PRODUCT CODE	SIZE	LOAD RANGE	SPEED RATING	TREAD DEPTH [32NDS]	SECTION WIDTH [IN]	OVERALL DIAMETER [IN]	MAX LOAD [IN]	MAX PRESSURE [PSI]	UTQG
10129680460	275 / 30R19	92	W	10	10.94	25.55	1389	51	360 AA
10129680320	245 / 35R20	91	V	10	9.76	26.77	1356	51	360 AA
10129680890	245 / 35R20	95	V	10	9.76	26.77	1521	51	360 AA
10129680390	245 / 35R20	95	W	10	9.76	26.77	1521	51	360 AA
10129680290	255 / 35R20	97	V	10	10.24	27.01	1609	51	360 AA
10129680550	255 / 35R20	97	W	10	10.24	27.01	1609	51	360 AA
10129680490	255 / 35R20	93	V	10	10.24	27.01	1433	51	360 AA
10129680710	255 / 30R22	95	V	10	10.24	28.07	1521	51	360 AA
10129680170	255 / 30R22	95	W	10	10.24	28.07	1521	51	360 AA
10129680830	265 / 35R22	102	V	10	10.67	29.33	1874	51	360 AA
10129680200	295 / 35R24	110	V	10	11.85	32.13	2337	51	360 AA
10129680900	305 / 35R24	112	V	10	12.32	32.44	2469	51	360 AA



TR967



Great Value All Season Tire

- Advanced tread design with multi-sipe for enhanced traction
- 3D shoulder profile offers excellent braking performance in dry and wet conditions
- Optimized tread block provides excellent winter performance

PRODUCT CODE	SIZE	LOAD RANGE	SPEED RATING	TREAD DEPTH [32NDS]	SECTION WIDTH [IN]	OVERALL DIAMETER [IN]	MAX LOAD [IN]	MAX PRESSURE [PSI]	UTQG
10129670040	205 / 55R16	91	H	10	8.43	24.88	1356	51	360 A A
10129670050	205 / 55R16	91	V	10	8.43	24.88	1356	51	360 A A
1012967060	205 / 55R16	94	H	10	8.43	24.88	1477	49	360 A A
1012967070	205 / 55R16	94	V	10	8.43	24.88	1477	49	360 A A
10129670410	205 / 50R17	89	W	10	8.43	25.12	1279	51	360 A A
10129670240	215 / 40R17	87	W	10	8.58	23.78	1202	49	360 A A
10129670290	215 / 45R17	87	W	10	8.39	24.65	1202	51	360 A A
10129670270	215 / 45R17	91	W	10	8.39	24.65	1356	49	360 A A
10129670280	215 / 55R17	94	W	10	8.90	26.30	1477	51	360 A A
10129670400	225 / 45R17	91	W	10	8.86	24.96	1356	51	360 A A
10129670420	235 / 45R17	94	W	10	9.29	25.35	1477	51	360 A A
10129670660	235 / 45R17	97	W	10	9.29	25.35	1609	49	360 A A
10129670470	235 / 50R17	100	W	10	9.65	26.30	1764	49	360 A A
10129670460	235 / 50R17	96	W	10	9.65	26.30	1565	51	360 A A
10129670630	235 / 40R18	91	W	10	9.49	25.39	1356	51	360 A A

TR967 | CONTINUED

PRODUCT CODE	SIZE	LOAD RANGE	SPEED RATING	TREAD DEPTH [32NDS]	SECTION WIDTH [IN]	OVERALL DIAMETER [IN]	MAX LOAD [IN]	MAX PRESSURE [PSI]	UTQG
10129670640	235 / 40R18	95	W	10	9.49	25.39	1521	49	360 AA
10129670620	245 / 40R18	93	W	10	9.76	25.71	1433	51	360 AA
10129670820	245 / 40R18	97	W	10	9.76	25.71	1609	49	360 AA
10129670490	245 / 45R18	100	W	10	9.57	26.65	1764	49	360 AA
10129670980	235 / 35R19	87	W	10	9.49	25.47	1202	51	360 AA
10129670990	235 / 35R19	91	W	10	9.49	25.47	1356	49	360 AA
10129670070	245 / 40R19	94	W	10	9.76	26.73	1477	51	360 AA
10129670080	245 / 40R19	98	W	10	9.76	26.73	1653	49	360 AA
10129670800	245 / 35R20	95	W	10	9.76	26.77	1521	49	360 AA



Passenger Tire Warranty

Thank you for choosing Triangle passenger tires. To ensure your 100% satisfaction with your Triangle tires, Triangle hereby warrants that every new Triangle is free from defects in workmanship or material for four (4) years from the date of manufacture (DOT code) or through the life of the original tread of a new tire less 2/32" of tread depth. The life of the original usable tread ends when the tire tread has worn down with only 2/32" remaining, at which point the tire is considered to be fully worn out.

60-Day 100% Total Satisfaction

If you are not 100% happy with your new Triangle tires, simply bring the tires and original purchase receipt back to the place where you bought the tires within 60 days of your purchase; we will gladly return your tires in the form of a store credit for future purchase with a minimum of 10% restocking fee.

Manufacture Defects

Triangle hereby warrants that every new Triangle tire is free from defects in workmanship or material and will be replaced 100% free of charge, within 12 months from the date of purchase, or within the first 2/32" (1.6mm) of original usable tread life, whichever comes first. After the 100% replacement term, if the tire is still within 48 months from date of manufacturer (DOT date) or through the life of the original tread of new tire less 2/32" of tread depth, a credit will be given toward the purchase of a comparable new tire. Credit amount will be determined by the percentage of original tread depth remaining on the tire. The costs of mounting, balancing and any other service charges including applicable taxes shall be borne by the owner.

What Is Not Covered

This warranty does not cover tires damaged due to misuse, abuse or accident listed below:

- Incorrect application, inappropriate mounting / dismounting of the tire, tire / wheel imbalance or improper repair
- Uneven or rapid wear caused by mechanical irregularity in the vehicle such as wheel misalignment
- Racing, off road use, under or over inflation, overloading
- Accident, fire, chemical corrosion, tire alteration or vandalism, flat spotting caused by improper storage or brake lock up
- The addition of liquid, solid or gaseous materials other than air, nitrogen or carbon dioxide
- Minor cosmetic ozone or weather cracking

Other limitations included but not limited to the following:

- Failure to rotate the tires as recommended voids the tread wear warranty
- Tires on vehicles operated outside the United States
- Any tires worn less than 2/32" remaining tread depth
- Tire which D.O.T. identification number and/or brand name removed intentionally
- Ride complaints after 2/32" of tread wear will not be accepted

Road Hazard Replacement Program

Triangle's 2-year road hazard warranty will protect you against non-repairable damage caused by puncture, snag, cut, bruise or impact break. Within the first 12 months of ownership, Triangle will replace with a Triangle tire 100% free of charge. In the second 12 months of ownership, Triangle will pay 50% of dealer's purchase price to replace with a Triangle tire.

To qualify for the road hazard program, a tire must not be past 25% of original treadwear. The costs of mounting, balancing and any other service charges including applicable taxes shall be borne by the owner.

What Is Not Covered

- Tire damage due to vandalism
- Tire damage due to an accident
- Tire is repairable according to Rubber Manufacturers Association (RMA) standards
- Tire damage or failure due to racing or off road use
- Tire damage or failure due to irregular wear caused by mechanical issues
- Tires transferred from the vehicle that they were originally installed on
- Tire damage due to use of snow chains or studs

Mileage Limited Warranty

For selected Triangle Ultra High Performance tires, if the tire reaches the end of usable tread life before the stated mileage warranty, Triangle will issue a replacement tire on a pro rata basis. In order to maintain the tread wear warranty, the tires must be rotated every 5,000 to 6,000 miles (8,000 – 10,000km), or as recommended by the vehicle manufacturer, whichever rotation period is less. Failure to rotate the tires as provided voids this warranty. The costs of mounting, balancing and any other service charges including applicable taxes shall be borne by the owner.

TH201 30,000 miles

TR967, TR968 40,000 miles

What Is Not Covered

This warranty does not cover tires damaged due to misuse, abuse or accident listed below:

- Incorrect application, inappropriate mounting / dismounting of the tire, tire / wheel imbalance or improper repair
- Uneven or rapid wear caused by mechanical irregularity in the vehicle such as wheel misalignment
- Racing, off road use, under or over inflation, overloading

- Accident, fire, chemical corrosion, tire alteration or vandalism, flat spotting caused by improper storage or brake lock up
- The addition of liquid, solid or gaseous materials other than air, nitrogen or carbon dioxide
- Minor cosmetic ozone or weather cracking

Other limitations included but not limited to the following:

- Failure to rotate the tires as recommended voids the tread wear warranty
- The mileage warranty on each rear tire will be half what is specified for tires that cannot be rotated as recommended by Triangle because the tire size on the front is different from that on the rear
- No tread wear warranty for tires used in commercial applications
- Tires on vehicles operated outside the United States
- Any tires worn less than 2/32" remaining tread depth
- Tire in which D.O.T. identification number and/or brand name removed intentionally
- Ride complaints after 2/32" of tread wear will not be accepted
- Winter tires must be used in winter months only, defined as a period beginning on or after September 1st of a given year and ending no later than April 30th of the following year. Documentation of the timing of the installation and removal of the tires each winter is needed to maintain coverage.

To File a Claim

To file a claim, the following information is needed:

- All claims must be presented to an authorized Triangle dealer
- Present the defective tire to an authorized Triangle dealer
- A copy of the original purchase receipt
- Complete and sign the Triangle tire claim adjustment form provided by Triangle tire dealer



TRIANGLE TIRE USA

117 SEABOARD LANE, STE F100

FRANKLIN, TN 37067

CUSTOMERSERVICE@TRIANGLETIREUS.COM

1.888.847.3745

WWW.TRIANGLETIREUS.COM