

E-3 / L-3

TB598

**Excellent Traction Radial
with Exceptional Reliability
in Haulage Applications**

Rugged shoulder design provides maximum durability on construction, aggregates and mining sites.



PRODUCT CODE	TIRE SIZE	LOAD SYMBOL	INDUSTRY CODE	OVERALL DIAMETER [INCH]	OVERALL WIDTH [INCH]	STATIC LOAD RADIUS [INCH]	MAX SPEED [MPH]	SINGLE MAX LOAD [LBS/PRESSURE]	TREAD DEPTH [32NDS]	MINIMUM DUAL SPACING [INCH]	RIM WIDTH & FLANGE	TT / TL	TMPH [T1]	TMPH [T2]	TMPH [T3]
10135980891	750/65R25	★★	E-3	63.4	29.7		30	23400/62	55		24.00/3.0	TL	89	130	171
10135980501	775/65R29	★★	L-3	68.7	30.4		5	28300/62	55		24.00/3.0	TL			
10135980501	775/65R29	★★	E-3	68.7	30.4		30	45400/91	55		24.00/3.5	TL	134	161	223
10135980541	875/65R29	★★	E-3	73.5	34.2	32.5	30	34200/62	63		28.00/3.5	TL	158	195	247

TB598 FEATURES & BENEFITS

Aggressive Self-cleaning Tread Pattern

For excellent traction, flotation and long tread life

Unique Compound

For long original tread life and efficient fuel economy

Rugged Shoulder Design

For enhanced sidewall protection

Tough Casing Construction

For enhanced impact and penetration resistance



QUALITY CONSTRUCTION - BACKED BY AN INDUSTRY LEADING WARRANTY



30-Day 100% Total Satisfaction Guarantee

Triangle is one of the world's largest OTR tire producers, favored by many heavy equipment OEMs. If you are not 100% happy with your Triangle OTR radials within 30 days of purchase, we will gladly exchange your tires for a full refund.

For more information, contact your local Triangle dealer, or visit TriangleTireUS.com.