



TR643

Special-Purpose Trailer Tire

Twin steel belt construction* provides exceptional traction, durability and highway stability.

**Selected sizes reinforced with nylon cap plies*



PRODUCT CODE	SIZE	PLY RATING	LOAD INDEX	SPEED RATING	TREAD DEPTH [32NDS]	STANDARD RIM	ALTERNATIVE RIM	SECTION WIDTH [IN]	OVERALL DIAMETER [IN]	MAX LOAD SINGLE / DUAL [LB]	MAX PRESSURE [PSI]	WEIGHT [LB]
10146430721	ST175/80R13	6	91/87	N	8	5J	4.5J, 5.5J	7	24.0	1356/1202	51	17
10146430431	ST205/75R14	6	100/96	N	8	5.5J	5J, 6J	8	26.1	1764/1565	50	23
10146430241	ST215/75R14	6	102/98	N	9	6J	5.5J, 6.5J	9	26.7	1874/1653	50	25
10146430281	ST205/75R15	6	101/97	N	8	5.5J	5J, 6J	8	27.1	1819/1609	50	24
10146430771	ST205/75R15	8	107/102	N	8	5.5J	5J, 6J	8	27.1	2150/1874	65	26
10146430711	ST225/75R15	8	113/108	N	9	6J	6.5J, 7J	9	28.3	2535/2205	65	29
10146430221	ST225/75R15	10	117/112	N	9	6J	6.5J, 7J	9	28.3	2833/2469	79	29
10146430811	ST235/80R16	10	124/120	N	8	6.5J	6J, 7J	9	30.8	3527/3086	79	36

TR643 FEATURES & BENEFITS

Symmetric Tread Design with a Solid Center Rib

Deliver dependable highway stability, traction and long tread wear

Rounded Profile

Improves trailer ride



Twin Steel Belt Construction*

Enhance traction and durability

** Selected sizes reinforced with nylon cap plies*

QUALITY CONSTRUCTION - BACKED BY AN INDUSTRY LEADING WARRANTY



90-Day 100% Total Satisfaction Guarantee

If you are not 100% happy with your new Triangle ST Radial tires, simply bring the tires and original purchase receipt back to the place where you bought the tires within 90 days of your purchase. We will gladly exchange your tires for a full refund.

For more information, contact your local Triangle dealer, or visit TriangleTireUS.com.