



TRT01S

All-Steel Special-Purpose Trailer Tire

All-steel construction provides exceptional durability and towing stability; 14 ply rating, M speed rated.



PRODUCT CODE	SIZE	PLY RATING	LOAD INDEX	SPEED RATING	TREAD DEPTH [32NDS]	STANDARD RIM	ALTERNATIVE RIM	SECTION WIDTH [IN]	OVERALL DIAMETER [IN]	MAX LOAD SINGLE / DUAL [LB]	MAX PRESSURE [PSI]	WEIGHT [LB]
1014T010170	ST235/80R16	14	129/125	M	10.5	6½J	6J, 6K, 6L, 6½J, 6½L, 7J, 7K, 7L, 7½J	9.25	30.8	4080/3640	110	57
1014T010070	ST235/85R16	14	132/127	M	13	6½J	6J, 6K, 6L, 6½J, 6½L, 7J, 7K, 7L, 7½J	9.25	31.7	4400/3860	110	61

TRT01S FEATURES & BENEFITS

Specially Designed Cool-Running Compound

Improves tread wear

Circumferential Grooves

Help deliver even and uniform wear



Solid Shoulder Ribs

Deliver even and uniform wear

All Steel Construction

Enhances durability and extends tread life

QUALITY CONSTRUCTION - BACKED BY AN INDUSTRY LEADING WARRANTY



90-Day 100% Total Satisfaction Guarantee

If you are not 100% happy with your new Triangle ST Radial tires, simply bring the tires and original purchase receipt back to the place where you bought the tires within 90 days of your purchase. We will gladly exchange your tires for a full refund.

For more information, contact your local Triangle dealer, or visit TriangleTireUS.com.